

CHAIN LINK FENCE

Chain Link Fence Sections:

Overview	Specifications	Warranty	Photo Gallery	Installation Instructions	Freight	Get a Quote	Shop Now
----------	----------------	----------	---------------	---------------------------	---------	-------------	----------

Galvanized Fabric Specifications

	12 1/2 Gauge	11 1/2 Gauge	11 Gauge
APPLICATIONS	Economy	Standard Residential	Light Commercial
MESH SIZE	2 3/8"	2 1/4", 2 3/8", 1 1/4"	2", 1 3/4"
COATING	Class III Galvanized before weaving	Class III Galvanized after weaving, Class III Galvanized before weaving (ideal for kennels, no burrs)	1.2 ounces of zinc coating per ft ²
HEIGHTS	36"-144"		
SELVAGE	Knuckle & Knuckle (36"-60"); Knuckle & Barbed (72" and higher)		
STANDARD ROLL	50 ft. per roll		
MEETS OR EXCEEDS	—	ASTM Spec. - A-392	Fed. Spec. - RR-F-191/1D ASTM Spec. - A-392 AASHTO Spec. - M-181
IDEAL USES	Light-weight residential fencing, Temporary construction fencing	Residential fencing, Kennel fencing, Swimming Pool fencing (1 1/4" mesh size)	Light-weight commercial fencing, Tennis Courts

Galvanized Framework Specifications

	Economy Residential Framework	Standard Residential Framework	Heavy Residential Framework
Wall Thickness	18 Gauge - .047"	17 Gauge - .055"	16 Gauge - .065"
Diameters	1 3/8", 1 5/8", 2", 2 1/2"		

commonly available			
Weight per foot Coating	.90 ounces of zinc per ft ²		
Ideal uses	Light-weight residential fencing , Temporary construction fencing	Residential fencing, Dog pens	Heavy Residential fencing , Dog pens, Light Commercial
Specifications	Available in mill length 21' or 24' (others on request) Cut Posts 5'6" to 8'6" (others on request) Swedged ends available on 1 3/8" & 1 5/8" rails Detail Specifications available on request	Available in mill length 21' or 24' (others on request) Cut Posts 5'6" to 8'6" (others on request) Swedged ends available on 1 3/8" & 1 5/8" rails Detail Specifications available on request	Available in mill length 21' or 24' (others on request) Cut Posts 5'6" to 8'6" (others on request) Swedged ends available on 1 3/8" & 1 5/8" rails Detail Specifications available on request
Meets or exceed the following specifications		ASTM Spec. - A-392	ASTM Spec. - A-392

Vinyl/Color Fabric Specifications

	11 Gauge - Swimming Pool	9 Gauge - Residential	8 Gauge - Commercial
CORE SIZE	.080	.095	.120
MESH SIZE	1 1/4"	2", 1 3/4", 1 1/4"	2", 1 3/4"
COATING	22 mils of PVC coating, Bonded to Core Wire	22-25 mils of PVC coating, Bonded to Core Wire	22 mils of PVC coating, Bonded to Core Wire
HEIGHTS	36"-144"		
SELVAGE	Knuckle & Knuckle (36"-60"); Knuckle & Barbed (72" and higher)		
STANDARD ROLL	50 ft. per roll		

MEETS OR EXCEEDS	Boca Code - swimming pools (48"+ only)	BOCA Code (for swimming pools chain link) - 1 1/4" - 48" & higher only	Fed. Spec. - RR-F-191/1D ASTM Spec. - F-668 Class 2A
COLORS	Black, Brown, Green, White, Woodland Green, Steel Gray		
IDEAL USES	Swimming Pools	Residential fencing, Light Commercial, Swimming Pools, Tennis Courts, Kennels	Commercial fencing, Tennis Courts

Vinyl/Color Framework Specifications

	Color Residential Framework	HT-25 Color Commercial Framework
Diameters & Wall Thickness commonly available	1 3/8" - (.055" wall thickness) 1 5/8" - (.065" wall thickness) 2" - (.065" wall thickness) 2 1/2" - (.065" wall thickness)	1 5/8" - (.0934 wall thickness) 2" - (.0934 wall thickness) 2 1/2" - (.1084 wall thickness) 3" - (.1233 wall thickness)
Weight per foot		1 5/8" - 1.588 lbs/ft 2" - 1.831 lbs/ft 2 1/2" - 2.638 lbs/ft 3" - 3.531 lbs/ft
Coating	Galvanized - .90 ounces of zinc per ft ² Epoxy Powder Coat - 2 mils "No-Mar" Polyester Color Coat - 2-3 mils	Galvanized - .90 ounces of zinc per ft ² Epoxy Powder Coat - 2 mils "No-Mar" Polyester Color Coat - 2-3 mils
Colors	Green Black Brown	Green Black Brown

Ideal uses	Residential fencing Light commercial fencing	Commercial Fencing Nurseries Mini-Storages Day Care Facilities Golf Courses Swimming Pools Apartments Playgrounds Tennis Courts Parking Lots Perimeter Security Athletic Fields
Specifications	Available in mill length 21' (or 22') or 24' (others on request) Cut Posts 6' to 10'6" (others on request) Swedged ends available on 1 3/8" & 1 5/8" rails Detail Specifications available on request	Available in mill length 21' or 24' (others on request) Cut Posts 6' to 13' (others on request) Swedged ends available on 1 5/8" rails Detail Specifications available on request
Meets or exceed the following specifications		